





Oceanic Steam Generator and Sauna heater Quotation



Item No	description	recommended steam/sauna room (M ³)	carton size (mm)	Quantity (sets) in			products photos	cijena (HRK s PDV)	Remarks
				20FT	40FT	40HQ			
Oceanic intelligent steam generator OC-A controller									
OC30	3kw/230v	2.5-5	445*240*455	585	1195	1325	  default control cabel length is 5m, 10m control cable need extra	4500,00	OC-A intelligent digital controller,Time setting between 15 and 240 minutes or no time limit ;Temp setting 30 to 60 °C. °C&°F display ;business mode and domestic mode. Sequential heating system. one controller control many steam generator ;Advanced digital signal control mode ;LED diagnostic system; Overheat and boil dry protection as standard ; 1.2BAR pressure relief valve ; real CE approved in UK by Nemko
OC40	4kw/230v	2.5-5	445*240*455	585	1195	1325		4650,00	
OC45	4.5kw	2.5-5	445*240*455	585	1195	1325		4750,00	
OC60	6kw	6-7	445*240*455	585	1195	1325		4900,00	
OC80	8kw	8-10	510*245*475	515	1035	1135		5200,00	
OC90	9kw	10-12	510*245*475	515	1035	1135		5450,00	
OC105	10.5kw	12-15	450*257*542	440	920	1030		6000,00	
OC120	12kw	14-17	450*257*542	440	920	1030		6500,00	


Oceanic intelligent steam generator-commercial type (with steam on demand function and link function)									
OCC30	3kw/230v	2.5-5	445*240*455	585	1195	1325		4890,00	<p>New "Steam on Demand" function on all commercial generators - allows the operator to set the steam generator to work on customer demand. The start button is located inside the steam room and when it pushed by the customer steam is produced for 30 minutes after which the generator will stop until the button is pushed by another customer saving energy and cost during periods of intermittent use. The steam on demand function can be turned on or off by the operator as and when required.need link function will add extra 10USD for each steam generator,real CE approved in UK by Nemko</p>
OCC40	4kw/230v	2.5-5	445*240*455	585	1195	1325		5040,00	
OCC45	4.5kw	2.5-5	445*240*455	585	1195	1325		5140,00	
OCC60	6kw	6-7	445*240*455	585	1195	1325		5290,00	
OCC80	8kw	8-10	510*245*475	515	1035	1135		5590,00	
OCC90	9kw	10-12	510*245*475	515	1035	1135		5840,00	
OCC105	10.5kw	12-15	450*257*542	440	920	1030		6390,00	
OCC120	12kw	14-17	450*257*542	440	920	1030		6890,00	

default control cabel length is 5m, 10m control cable need extra

Oceanic intelligent steam generator Heavy duty OC-B series (with auto descaling ,steam on demand function and link function)									
OC30B	3kw/230v	2.5-5	580*230*460	500	1040	1144		5980,00	<p>Heavy duty model with auto-descaling and fast-steaming ,energysaving function, 3KW to 18KW 2 YEAR Limited warranty ,New "Steam on Demand" function on all commercial generators - allows the operator to set the steam generator to work on customer demand. The start button is located inside the steam room and when it pushed by the customer steam is produced for 30 minutes after which the generator will stop until the button is pushed by another customer saving energy and cost during periods of intermittent use. The steam on demand function can be turned on or off by the operator as and when required.need steam on demand have extra 10USD ,link function will add extra 10USD for each steam generator.</p>
OC40B	4kw/230v	2.5-5	580*230*460	500	1040	1144		6060,00	
OC45B	4.5kw	2.5-5	580*230*460	500	1040	1144		6240,00	
OC60B	6kw	6-7	580*230*460	500	1040	1144		6420,00	
OC80B	8kw	8-10	580*260*500	432	864	960		6710,00	
OC90B	9kw	10-12	580*260*500	432	864	960		7000,00	
OC105B	10.5kw	12-15	580*260*500	432	864	960		7700,00	
OC120B	12kw	14-17	580*260*500	432	864	960		8086,00	
OC135B	13.5kw	15-18	580*280*590	336	640	720		8606,00	
OC150B	15kw	17-20	580*280*590	336	640	720		8866,00	
OC180B	18kw	19-24	580*280*590	336	640	720		9126,00	



default control cabel length is 5m, 10m control cable need extra

Stainless steel Oceanic intelligent steam generator Heavy duty OC-B series (with auto descaling , steam on demand function and link function)									
OC30BST	3kw/230v	2.5-5	580*230*460	500	1040	1144		7020,00	<p>Heavy duty model with auto-descaling and fast-steaming ,energysaving function, 3KW to 18KW</p> <p>2 YEAR Limited warranty</p> <p>,New "Steam on Demand" function on all commercial generators - allows the operator to set the steam generator to work on customer demand. The start button is located inside the steam room and when it pushed by the customer steam is produced for 30 minutes after which the generator will stop until the button is pushed by another customer saving energy and cost during periods of intermittent use. The steam on demand function can be turned on or off by the operator as and when required.need steam on demand have extra 10USD ,link function will add extra 10USD for each steam generator.</p>
OC40BST	4kw/230v	2.5-5	580*230*460	500	1040	1144		7120,00	
OC45BST	4.5kw	2.5-5	580*230*460	500	1040	1144		7280,00	
OC60BST	6kw	6-7	580*230*460	500	1040	1144		7540,00	
OC80BST	8kw	8-10	580*260*500	432	864	960		8060,00	
OC90BST	9kw	10-12	580*260*500	432	864	960		8320,00	
OC105BST	10.5kw	12-15	580*260*500	432	864	960		9100,00	
OC120BST	12kw	14-17	580*260*500	432	864	960		9360,00	
OC135BST	13.5kw	15-18	580*280*590	336	640	720		10140,00	
OC150BST	15kw	17-20	580*280*590	336	640	720		10400,00	
OC180BST	18kw	19-24	580*280*590	336	640	720	10920,00		
. default control cabel length is 5m, 10m control cable need extra									
Steam nozzle Guard									
OC-SNG	steam nozzle guard (prevent from scalding and hot steam blowing to acrylic directly)						260	made of stainless steel and tempered glass	
3 Way Fragrance pump (steam Aroma)									

OC-EP	3 way fragrance pump	suit for any steam room ,can works with any steam generator	310*150*295	2280	4600	5170	 <p>user need buy the containers from local as exist container is too big and not economical to ship them</p>	2600 (buy Oceanic steam generator together is 2300)	<p>Automatic temperature sensor - pump only operate when the generator is steaming.</p> <p>3 Ways - the pump has 3 inlet valves to enable 3 different fragrances to be injected into the steam line - select anyone of the 3 or an alternating sequence.</p> <p>Variable settings for different steam room sizes and various fragrance concentrations.</p> <p>Variable interval settings to maximize efficiency.</p> <p>Built in non return valve & a run dry sensor to protect the pump .</p> <p>Supplied complete with 9V mains adapter, not including fragrance and container</p>
-------	----------------------	---	-------------	------	------	------	--	---	--

--	--	--	--	--	--	--	--	--	--

OCS B series sauna heater

OCS090B	9kw	9-13	670*500*660m m	105	213	284		5400,00	<p>SUS304 stainless steel jacket ,interlegient controller with separete control box,2 sets of independant contacts for the thermostatic control and the thermal cut out. .Tep setting 50-110°C or 122-230°F . Intelligent Sequential heating system, double over heat protection system for both sauna room and sauna heater.LED diagnostic system, interlock function comply with the new CE standard</p>
OCS105B	10.5kw	10-15		105	213	284		5600,00	
OCS120B	12kw	11-18		105	213	284		5800,00	
OCS150B	14.1kw	12-22		105	213	284		6200,00	
OCS170B	16.2kw	14-25		105	213	284		6500,00	
OCS180B	18kw	17-29	725*565*675	96	192	243		7200,00	
OCS210B	20.1KW	20-34		96	192	243		7600,00	
OCSB	control panel for 9-16.2kw stand type three phase /400v							2200,00	

USD

control box for 9-25kw stand type three phase /400v



DCC-8 ControlBox

2600,00

Remarks:

1. the recommended steam /sauna room is just for reference , choose right steam generator or sauna heater for steam room or sauna room need consider the steam room material. if has the heat isolation .environment temperature